

# 3 3/4" Open Hole Serpentine Flex Joint

Product Reference: 050-FA120-0000

The Serpentine Flex Joint allows tool combinations which require both eccentric and centralized orientation.

The open-hole flex joint combines strength and flexibility in one package, allowing tools such as the eccentric compensated neutron tool to be run together with a centralized bore hole compensated sonic tool.



## SPECIFICATIONS - 3 3/4" OPEN-HOLE SERPENTINE FLEX JOINT

<b>Diameter</b>	3 3/4"	9.5 cm	<b>Mechanical:</b>	
<b>Length</b>	66"	1.7 m	<b>Top Connection</b>	17 pin GOI type
<b>Weight</b>	146 lb.	66.4 kg	<b>Bottom Connection</b>	17 pin GOI type

### Limitations:

<b>Maximum pull strength</b>	60,000 lb.	27,250 kg
<b>Maximum tool offset</b>	4"	10.2 cm

<b>Maximum Pressure</b>	20,000 psi	137.9 MPa
<b>Maximum Temperature</b>	350°F	177°C

## RELATED PRODUCTS

- 035-AS00-021 Vertical make-up plate

At Probe, we design, manufacture and service specialized modular downhole tools and systems. Our tools are used in formation evaluation, well integrity assessment and well productivity determination across the global energy industry.

© 2010 Probe Holdings, Inc. All rights reserved.

Probe Technology Services Inc • 1132 Everman Parkway • Fort Worth • Texas 76140 • USA • T +1 817 568 8528 • F +1 817 568 0091 • [www.probe1.com](http://www.probe1.com)