

1 11/16" Casing Collar Locator

Product Reference: 050-CC170-0000

The Casing Collar Locator (CCL) is used to correlate casing or tubing collars for depth accuracy purposes.

The dual magnet center coil Casing Collar Locator (CCL), with a powered amplified signal, provides maximum sensitivity in up to a 7-inch diameter casing and is readily combinable with other Probe tools that do not typically have an integral CCL such as tracer ejector stacks and free point indicators.

SPECIFICATIONS - 1 11/16" CASING COLLAR LOCATOR

Diameter	1 11/16"	4.3 cm	Mechanical:	
Length	27"	0.69 m	Top Connection	GOI Single Pin Box
Weight	12.5 lb.	5.6 kg	Bottom Connection	GOI Single Pin Male
Operating Voltage	100 VDC		Note: Other connection types available upon request.	
Operating Current	12 mA. DC			

Limitations:

Maximum Pressure	20,000 psi	137.8 MPa
Maximum Temperature	350°F	177°C

RELATED PRODUCTS

- 050-CBN170-1000x 1 11/16" Dual Receiver Cement Bond Log Tool
- 050-CB170-1000D 1 11/16" Dual Receiver Digital Cement Bond Log Tool
- 050-RADII-170 1 11/16" RADII™ Dual Receiver Cement Bond Log Tool
- 050-GR170-0000 1 11/16" Gamma Ray/CCL Tool
- 050-NU170-0000 1 11/16" Neutron Tool

Note: x represents variable for configuration, product reference.



At Probe, we design, manufacture and service specialized modular downhole tools and systems. Our tools are used in formation evaluation, well integrity assessment and well productivity determination across the global energy industry.