ONLINE TECHNICAL SPECIFICATION SHEET



ARRAY GAS HOLD UP TOOL - HD - 1 11/16 IN.





SKU: AGH001

Categories: Array Production Logging, Cased Hole Wireline, HD Platform™,

Production Logging

PRODUCT DESCRIPTION

The Array Gas Hold Up Tool (AGH001) is a 6 sensor Optical Array Gas Hold Up tool. Both gas hold up and bubble count are provided by each sensor.

The opening diameter can be restricted to avoid contamination from debris on the casing wall and to help avoid damage in open hole. Adjustment is continuous and any diameter can be set.

The AGH can be combined with the RAS, PL and Array (Capacitance, Resistance, Fluid Velocity) and is supported in SRO and memory modes.

Ratings & Dimensions

Max temperature 302°F (150°C)

 Max pressure
 15,000 psi (103.4 mPa)

 Outer diameter
 1.69 in (43.0 mm)

 Length
 45.5 in (1155.7 mm)

Weight 15.43 lb (7.0 kg)

Materials Corrosion resistant materials used throughout

Sensor Specifications

Range Adjustable up to 7" **Measure points** 16.0in (406.4 mm)

Hardware Characteristics

Combinability All HD tools (RADii, iQ, PL, RAS, etc)

Acquisition Mode Real-time (with TCU) Memory (with MLT)



ONLINE TECHNICAL SPECIFICATION SHEET



Electrical Specifications

Current 12mA @ 50V 26mA @ 19V

Version Control: 2021.11.17

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.