


GAMMA RAY & CASING COLLAR LOCATOR - HD - 2 3/4 IN.



SKU: GCL003
Categories: [Cased Hole Wireline](#), [Gamma Ray & CCL](#), [HD Platform™](#), [Well Intervention](#)

PRODUCT DESCRIPTION

The Gamma Ray & Casing Collar Locator (GCL003) is a combined Gamma Ray & CCL tool which provides a passive measurement of gamma radiation by means of a Sodium Iodine Scintillation Detector and identifies changes of metal thickness by means of a collar locator.

Ratings & Dimensions

Max temperature	350°F (177°C)
Max pressure	15,000 psi (103.4 mPa)
Outer diameter	2.75 in (70.0 mm)
Length	36.7 in (933.0 mm)
Weight	34.0 lb (15.6 kg)
Measure Points	Gamma Ray: 8.48 in (215.0 mm)
Materials	Casing Collar: 28.9 in (735.0 mm) Corrosion resistant materials used throughout

Measurements

Range	1-65,000 cps
Resolution	1 cps
Accuracy	10%
Sensitivity	(nominal) 1 count / API

Hardware Characteristics

Combinability	All HD tools (RADii, iQ, PL, RAS, etc)	
Acquisition Mode	Real-time (with TCU)	Memory (with MLT)



Electrical Specifications

Voltage	50V DC	19V DC
Current	10 mA	24 mA

Version Control: 2021.12.14

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.