

INTELLEX™ DYNAWELL LOW POWER ELECTRONIC  
TRIGGER - 1 3/8 & 1 11/16 IN.



**SKU:** SEN-0010-0325, SEN-0010-0326, SEN-0010-0309 and SEN-0010-0310  
**Categories:** [Cased Hole Wireline](#), [Firing Heads - Triggers](#), [Intellex™](#),  
[Perforating](#), [PTX](#), [Well Intervention](#)

PRODUCT DESCRIPTION

Intellex™ DYNAWELL Low Power Electronic Triggers are battery powered low power electronic firing heads used to initiate the detonation of ballistic devices with the highest degree of safety and control.

Ratings & Dimensions

Tool type	1.375 OD Firing Head	1.69 OD Firing Head
Part Number	SEN-0010-0325	SEN-0010-0309
Max temperature	347°F (175°C)	
Max pressure	15,000 psi (103.4 mPa)	
Outer diameter	1.375 in (34.9 mm)	1.690 in (43.0 mm)
Length	46.0 in (1.17 m)	
Weight	22.0 lbs (9.9 kg)	
Max Tensile Load	20,000 lbs (9,000 kgs)	30,000 lbs (13,600 kgs)
Materials	Corrosion resistant materials used throughout	

Hardware Characteristics

Housing	17-4PH (standard) or NACE MR-01-75 Compatible
Connection	Top: 15/16 in x 10 UN (5/8 in Sucker Rod) Bottom: 1 3/16 in x 12 UNF GO Pin
Supported Devices	DYNAWELL Electronic Detonators & Igniters (RF Safe Devices) HPI/TTS Low Voltage Solenoid (same module as DYNAWELL)

Temperature Measurements

<b>Range</b>	0 - 165°C ( 32- 329°F)
<b>Accuracy</b>	< $\pm 0.5^{\circ}\text{C}$
<b>Resolution</b>	< $0.01^{\circ}\text{C}$ @ 1 sps

## Pressure Characteristics

<b>Range</b>	0 - 15000psi (0 - 103.42MPa)
<b>Accuracy</b>	< $\pm 0.05\%$ FS
<b>Resolution</b>	0.01 psi @ 10,000 psi & 1 sps

## Acceleration

<b>Accuracy</b>	$\pm 0.1$ g
<b>Resolution</b>	< 0.01 g

## Electrical Specification

	Module A	Module C & D
<b>Battery</b>	2 x PMX165 'C' Lithium battery	
<b>Voltage (DC)</b>	5-9Vdc, power supplied via USB or 2 x 'C' cell Lithium battery pack.	
<b>Memory Rate</b>	145.5 hrs/6.06 days @ 1 sps	18.2 hrs/0.75 days @ 1 sps
	Modules C & D can be sampled at slower speeds allowing up to 30 days logging. EFH will continue to function even if the memory is full.	
<b>Consumption</b>	10mA Max Logging, 2A Max Firing Current	
<b>Shock</b>	> 500 g	
<b>Shooting CCL</b>	500 $\mu\text{A}$ (Idle); 8 sps, stored 1 sps to memory	

Version Control: 2022.02.15

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***