


CABLE PROTECTORS



SKU: 18700-641
Categories: [Advanced Monitoring](#), [Ancillary](#), [Downhole Gauges](#), [Downhole Instrumentation](#), [Gauges](#), [Kuster®](#), [Well Monitoring](#)

PRODUCT DESCRIPTION

Cross-coupling Cable Protectors are installed to secure the permanent downhole cable to the production tubing. They are typically installed on the coupling of the production tubing, designed to protect and support the downhole cable from physical damage during installation and throughout the life of the well.

Mid-Joint clamps are also available with the same specification as the clamps below, these clamps do not fit across the production tubing coupling.

Hardware Characteristics

Tubing Size	Typical - 2-3/8", 2 7/8ths, 3 1/2" & 4-1/2" (other clamps are available on request)
Combinability	TEC bare/encapsulated & Capillary
Configuration	Round or Square TEC
Bolts	Captivated M10 Bolts to be torqued to 30ft/lbs
Cable Slots	Cable slots option vary to suit the completion requirements
Materials	Cast steel or pressed metal construction

Features & Benefits

- One piece assembly with chamfered ends
- Fastener designs ensure fast and safe installation
- Protector to be butted up against the downhole end of the coupling
- No loose parts
- Slim hole casing designs are available
- Low risk of hang up while running in hole
- Quick and easy to install.

Version Control: 2021.12.22



On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.