


SHOOTING CASING COLLAR LOCATOR - AES - 1 11/16 IN.



**SKU:** SCL002

**Categories:** [Cased Hole Wireline](#), [Perforating](#), [PTX](#), [Shooting CCLs](#), [Well Intervention](#)

PRODUCT DESCRIPTION

Ratings & Dimensions

|                  |                      |
|------------------|----------------------|
| Max Temperature  | 350°F (177°C)        |
| Maximum Pressure | 20,000 psi (138 MPa) |
| Outer Diameter   | 1.69 in (42.93 mm)   |
| Length           | 14.25 in (361.95 mm) |
| Weight           | 7.5 lb (3.42 kg)     |

Borehole Conditions

|                 |                     |
|-----------------|---------------------|
| Borehole Fluids | Salt, Fresh and Oil |
|-----------------|---------------------|

Hardware Characteristics

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Connections* | <b>Top:</b> 1 3/16" 12P GO Box<br><b>Bottom:</b> 1 3/16" 12P GO Box |
|--------------|---------------------------------------------------------------------|

Electrical Specification

|              |       |
|--------------|-------|
| Voltage (DC) | 130V  |
| Current      | 22 mA |

Measurements

|                   |                         |
|-------------------|-------------------------|
| Data Transmission | Analog, Line Wobble, mV |
|-------------------|-------------------------|



\*Alternative connections available upon request.

Version Control: 2022.02.28

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***