

PROSHOOTER™ PANEL - DUMP FIRE



SKU: 035-WAR00-00DF

Categories: [Cased Hole Wireline](#), [Perforating](#), [ProShooter](#), [PTX](#), [Shooting Panels](#), [Surface Systems](#), [Well Intervention](#)

PRODUCT DESCRIPTION

The Probe ProShooter™ Panel is fully compliant with API RP-67 surface system requirements. It is Probe’s rack-mounted shooting panel solutions for safely providing shooting voltage and current to all type of downhole detonating devices used in the oilfield.

General Specifications

Width	3.5 in (88.9 mm)
Height	19.0 in (482.6 mm)
Depth	14.0 in (355.6 mm)
Weight	28.8 lbs (13.1 kg)

Electrical Specifications

Power Supply	110 - 120V AC
Voltage Output	0 to 500 V (Open Circuit Voltage)
Current Output	0 to 2.0 A
Power Supply Freq	50-60 Hz Single Phase, 2 Wire plus Ground
Output Current	2.0 A
Output Ripple (rms)	<2% @ ±350 VDC 2 A
Output Noise (p-p)	<1% @ ±350 VDC 2 A
Max Power Output	400 W (Non-continuous, load dependent)

Environmental Specifications

Operating Temperature	14.0 to 131.0 °F (-10.0 to 55.0 °C)
-----------------------	--



Features

Dump-Fire Capability  
Filter Board

Version Control: 2022.08.08

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***