# ONLINE TECHNICAL SPECIFICATION SHEET

# PROSHOOTER™ PANEL - DUMP FIRE - USB - PORTABLE



**SKU:** 035-WAR00-PORT
**Categories:** Cased Hole Wireline, Perforating, ProShooter, PTX, Shooting Panels, Surface Systems, Well Intervention

## PRODUCT DESCRIPTION

The Probe ProShooter™ Panel is fully compliant with API RP-67 surface system requirements. It is Probe's rack-mounted shooting panel solutions for safely providing shooting voltage and current to all type of downhole detonating devices used in the oilfield. This version allows for portability.

### General Specifications

| | |
|---|---|
| **Width** | 3.5 in (88.9 mm) |
| **Height** | 19.0 in (482.6 mm) |
| **Depth** | 14.0 in (355.6 mm) |
| **Weight** | 28.8 lbs (13.1 kg) |

### Electrical Specifications

| | |
|---|---|
| **Power Supply** | 110 – 120V AC |
| **Voltage Output** | 0 to 500 V (Open Circuit Voltage) |
| **Current Output** | 0 to 2.0 A |
| **Power Supply Freq** | 50-60 Hz Single Phase, 2 Wire plus Ground |
| **Output Current** | 2.0 A |
| **Output Ripple (rms)** | <2% @ ±350 VDC 2 A |
| **Output Noise (p-p)** | <1% @ ±350 VDC 2 A |
| **Max Power Output** | 400 W (Non-continuous, load dependent) |

### Environmental Specifications

| | |
|---|---|
| **Operating Temperature** | 14.0 to 131.0 °F<br>(-10.0 to 55.0 °C) |



© Copyright Probe Technologies Holdings, Inc.
All Rights Reserved.

# ONLINE TECHNICAL SPECIFICATION SHEET

**Features**

- Portable
- USB Interface Board
- Dump-Fire Capability
- Filter Board

Version Control: 2022.08.08

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***



© Copyright Probe Technologies Holdings, Inc.
All Rights Reserved.