

WELLHEAD OUTLET



SKU: 500-0043
Categories: [Advanced Monitoring](#), [Ancillary](#), [Downhole Gauges](#), [Downhole Instrumentation](#), [Gauges](#), [Kuster®](#), [Well Monitoring](#)

PRODUCT DESCRIPTION

The Wellhead Outlet connects the permanent downhole cable (TEC Line) to an armored surface cable while isolating the electrical connection in an explosion-proof housing, and provides a dual safety barrier to prevent well fluid migration to the surface. High-quality Swagelok fittings are an integral part of the design.

Ratings & Dimensions

Max pressure	15,000 psi
TEC line fittings OD	Standard 1/4" OD (Other sizes to order)
Length	15.78"
Weight	10.0 lbs (1.36 kgs)
Mounting	1/2" Male NPT (Other sizes to order)
Materials	316 SS
Pressure Test	Field pressure testable to 5k psi

Electrical Specification

Voltage	24 vDC
Standards met	NEC/CEC:Class I, Division 1 & 2, Groups B, C, D;Class II, Division 1, Groups E, F, G;Class II, Division 2, Groups F, G Class III;UL Standard: 1203;ANSI Standard: C33.27;CSA Standard: C22.2 No. 30;NEMA/EEMAC 3, 4

Version Control: 2021.12.22

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.

