SHOOTING CASING COLLAR LOCATOR - AES - 3 1/8 IN.



SKU: SCL005
Categories: Cased Hole Wireline, Perforating, PTX, Shooting CCLs, Well Intervention

PRODUCT DESCRIPTION

Ratings & Dimensions

Max Temperature	350°F (177°C)
Maximum Pressure	20,000 psi (138 MPa)
Outer Diameter	3.125 in (76.20 mm)
Length	19.00 in (482.60 mm)
Weight	34.0 lb (15.42 kg)

Borehole Conditions

Borehole Fluids	Salt, Fresh and Oil

Hardware Characteristics

Connections*	**Top:** 1 3/16” 12P GO Box **Bottom:** 1 3/16” 12P GO Box

Electrical Specification

Voltage (DC)	130V
Current	22 mA

Measurements

Data Transmission	Analog, Line Wobble, mV

© Copyright Probe Technologies Holdings, Inc.
All Rights Reserved.

ONLINE TECHNICAL SPECIFICATION SHEET

*Alternative connections available upon request.

Version Control: 2022.02.28

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.

© Copyright Probe Technologies Holdings, Inc.
All Rights Reserved.