Technical Specification Sheet

RADii® Cement Bond Tool - HD - 3 1/2 in.

The large diameter RADii® HD Segmented Cement Bond Tool uses a single ceramic transmitter, a sixteen segment receiver at 3 ft. and a single receiver at 5 ft. spacing. The segmented receiver generates a cement map which enables identification of cement channeling while the single receiver generates the traditional cement bond log (CBL) and a variable-density log (VDL).

Ratings & Dimensions

Max Temperature	350°F (177°C)
Maximum Pressure	15,000 psi (103.42 MPa)
Outer Diameter	3.5 in (88.90 mm)
Length	9.35 ft (2.82 m)
Weight	175.0 lb (79.40 kg)
Tensile Strength	**Tension:** 40,000 lb **Compression:** 40,000 lb
Materials	SST
Measure Points	**Amplitude, TT:** 4.3 ft (1.3 m) **VDL, Signature:** 3.3 ft (1.0 m)

Borehole Conditions

Borehole Fluids	Salt, Fresh and Oil
Tool Positioning	Centralized with one each centralizer above and below

Hardware Characteristics

Source Type:	One piezoelectric crystal fired at 18 kHz, 50 msec intervals
Sensor Type	**Omni Receiver:** One 18 kHz piezoelectric **Radial Receiver:** One 16 segment 18 kHz piezoelectric
Fire Rate	20/sec
Waveform	**Analog:** 3 ft (.9 m), 5 ft (1.5 m), **Digital:** Telemetry Data
Record Time	1400µs for each receiver, 500 µs for each sector
Combinability	GR, CCL, ProMac, iQ, Temperature
Connections	**Top:** GOI box **Bottom:** GOI pin
Acquisition Mode	SRO w/ TCU Mem w/ MLT

Electrical Specification

Current	82 mA @ 130V

Measurements

	E_1 Peak Amplitude	Sonic Waveform
Principle	Sonic Wavetrain Attenuation	
Range	200 to 1500µs	
Resolution	3 ft (.9 m)	5 ft (1.5 m)
Precision (1 SD)	< 1mV	NA
Primary Curves	Amplitude 3ft (.9 m); Individual Sector Amplitudes (3 ft) (.9 m) TT 3 ft (.9m); VDL 5 ft (1.5 m)	
Secondary Curves	Head Voltage, Internal Temperature, Accelerometer, Volume	

Calibration

Primary	9 5/8 in. (24.4 cm) Pressurized calibration tank
Wellsite Verifier	Free Pipe, Stored Calibration Tank Waveforms from memory

© Copyright 1994-2021 Probe Technologies Holdings, Incorporated. All Rights Reserved. | Specifications may change without notice. | 050-RB350-1000