Technical Specification Sheet

Gamma Gun - Scintillation - Single Fire - 3 1/8 in.

The single fire Gamma Gun is a ruggedized tool fitted with a Scintillation GR detector on the lower section of the tool and a passive CCL at the top. The tool is designed to be run with a Shooting Adapter at the bottom to suit the client's choice of gun system.

Ratings & Dimensions

Max Temperature	350°F (177°C) for 4 hours
Maximum Pressure	18,000 psi (124 MPa)
Outer Diameter	3.125 in (79.375 mm)
Length	57.12 in (1450.85 mm)
Weight	67.0 lb (30.0 kg)
Min Csg/Tbg OD	3.5 in (88.9 mm)
Max Csg/Tbg OD	11.75 in (298.45 mm)
Measurement Points	**Gamma Ray:** 13.5 in (342.9 mm) **Casing Collar Locator:** 47.65 in (1210.31 mm)
Tensile Strength	**Tension:** 60,000 lb **Compression:** 25,000 lb **Torque:** 150 lb ft (203 N-m)

Borehole Conditions

Borehole Fluids	No Restrictions
Tool Positioning	Centralized | Eccentralized

Measurements

	Gamma Ray	Casing Collar Locator
Sensor Type	NaI(Ti) Scintillation Gamma	Dual Magnet, Center Coil
Principle	Naturally Occurring Gamma	Magnetic Flux Variation
Sensor Spacing	Proprietary	
Sensitivity	Approximately 1.6 counts/API unit	
Range	0 to 5,000 cps	
Vertical Resolution	14.00 in (355.6 mm)	
Precision	5% at 100 GAPI at 15 fpm (4.6 m/min)	
Data Transmission	Analog, Pulse, + Polarity	Analog, Line Wobble, mV
Logging Speed	**Maximum:** About 30 ft (9 m) /min to 45 ft (9 to14 m) /min	
Sample Rate	4 to 10 samples/ft (10 to 40 samples/meter)	

Calibration

Primary	Approx. 1.0 cps/GAPI unit
Secondary	Thorium sleeve, API calibrated
Wellsite Verifier	Thorium sleeve, API calibrated

Electrical Specifications

Cablehead Voltage	60 V DC Internally Regulated
Instrument Current	60 mA
Shooting Polarity	Single

© Copyright 1994-2021 Probe Technologies Holdings, Incorporated. All Rights Reserved. | Specifications may change without notice. | 050-GG313-10DF