Technical Specification Sheet

ProMAC™ 60 | Multi-Arm Caliper Tool - PTX - 3 3/4 in.

The latest generation ProMAC™ series 60-arm caliper tool incorporates a series of mechanical, electrical and electronic design features that greatly increase tool accuracy, reliability, maintainability and overall cost efficiency.

Ratings & Dimensions

Max Temperature	350°F (177°C)
Max Pressure	20,000 psi (138 MPa)
Diameter	3.75 in (95.3 mm)
Length	65.49 in (1,663 mm)
Weight	102 lb (46.3 kg)
Tensile Strength	**Connection:** 15,000 lbF **Body:** 20,000 lbF
Measure Points	**Caliper:** 34.48 in (876 mm) from bottom of tool **Inclination:** 54.1 in (1374 mm) from bottom of tool
Materials	Corrosion resistant materials used throughout

Hardware Characteristics

Sensor Type	**Inclinometer:** 3-axis accelerometer
	Caliper: Differential Variable Reluctance Transducer
Combinability	All PTX tools: GR, CCL, iQ, RADii
Tool Positioning	Centralized
Acquisition Mode	SRO Only

Electrical Specification

Voltage	120V DC
Current	15mA(log) 40mA(opening)

Caliper Measurements

Sampling Rate	10 sps
Vertical Resolution	0.3 in (7.6 mm)
Radial Resolution	0.001 in (0.025 mm)
Logging Speed	30 ft/min (9 m/min)
Radial Accuracy	+/- 0.02 in (+/- 0.5 mm)
Diameter Range	3.80 in (96.5 mm) to 11.75 in (298.5 mm) – standard arms
Primary Output	60 independent radii measurements
Secondary Output	Head voltage, internal temperature, accelerometer

Accelerometer Measurements

	Inclination	Relative Bearing
Range	0° to 180°	0° to 360°
Accuracy	+/- 1.0°	+/- 1.0°
Resolution	+/- 0.1°	+/- 0.1°

Calibration

Primary / Wellsite	Precision machined calibration bowl

© Copyright 1994-2021 Probe Technologies Holdings, Incorporated. All Rights Reserved. Specifications may change without notice. | 050-MAC60-1000/1100