Technical Specification Sheet

Helical 4-Arm Centralizer | High Temp - 1 11/16 In.

The Helical 4-Arm Centralizer (HAC001-HT) provides a constant force across its opening range and centralization in vertical, deviated or horizontal wells. Operates in tubing or casing up to 9 5/8". The HAC001-HT is designed to place the rollers precisely where they need to be.

Tungsten Carbide rollers with replaceable bushes allow for extended service life and the tool is fitted with Elgiloy springs as standard.

The standard tool can be supplied with GO or GOI connections.

Ratings & Dimensions

Max temperature	572°F (300°C)
Max pressure	15,000 psi (103.4 mPa)
Outer diameter	1.69 in (43.0 mm)
Length	30.32 in (770.0 mm)
Weight	12.3 lb (5.6 kg)
Materials	Corrosion resistant materials used throughout
Measurement Range	Up to 9 5/8" (244.5 mm) casing

Features

Reduction of drag / friction during well entry
Can be supplied with sucker rod connections for slickline runs
Can be supplied with client specified connections
1 3/16" - 12UN - GO threads (Pin x Box Threads)

© Copyright 1994-2020 Probe Technologies Holdings, Incorporated. All Rights Reserved. | Specifications may change without notice. | HAC001-HT