Technical Specification Sheet

Cement Bond Tool - 2 3/4 in.

The Cement Bond Tool (CBT) uses a single acoustic transmitter and dual acoustic receivers spaced at 36 in. (91.44 cm.) and 60 in. (152.4 cm.) to accurately measure the quality of the cement job in a cased-hole environment.

Ratings & Dimensions

Max Temperature	350°F (177°C)
Maximum Pressure	20,000 psi (138 MPa)
Outer Diameter	2.75 in (69.85 mm)
Length	8.92 ft (2.72 m)
Weight	98.0 lb (44.46 kg)
Tensile Strength	**Tension:** 50,000 lb **Compression:** 35,000 lb
Materials	Corrosion resistant materials used throughout
Measure Points	**Amplitude, TT:** 4.3 ft (1.3 m) **VDL, Signature:** 3.3 ft (1.0 m)

Borehole Conditions

Borehole Fluids	Salt, Fresh and Oil
Tool Positioning	Centralized with one each centralizer above and below
Logging Speed	**Recommended:** 60 ft (18.2 m) /min **Max:** 100ft (30.5m) /min @ 0.08 ft (.02 m) sample rate

Hardware Characteristics

Source Type:	One piezoelectric crystal fired at 20 kHz, 50msec interval
Sensor Type	**Omni Receiver:** One 20 kHz piezoelectric
Fire Rate	20/sec
Waveform	**Analog:** 3 ft (.9 m), 5 ft (1.5 m), **Digital:** Telemetry Data
Record Time	1300µs for each receiver, 250 µs for each sector
Connections	**Top:** 1 3/16" 12P type "A" GO box **Bottom:** 1 3/16" 12P type "A" GO box
Combinability	GR, CCL, Neutron, Temperature

Electrical Specification

Current	38 mA @ 100V

Measurements

	E_1 Peak Amplitude	**Sonic Waveform**
Principle	Sonic Wavetrain Attenuation	
Range	200 to 1500µs	
Resolution	3 ft (.9 m)	5 ft (1.5 m)
Precision (1 SD)	< 1mV	NA
Primary Curves	Amplitude 3ft (.9 m); TT 3 ft (.9m); VDL 5 ft (1.5 m)	
Secondary Curves	None	

Calibration

Primary	5.5in. (13.97cm) Pressurized calibration tank
Wellsite Verifier	Free pipe

Other Options:
050-CB275-1350M: Digital CBL W/1553 Telemetry
050-CB275-1350MS: Digital CBL W/1553 Telemetry, SST

© Copyright 1994-2020 Probe Technologies Holdings, Incorporated. All Rights Reserved. | Specifications may change without notice. | 050-CB275-1350C