Technical Specification Sheet

Fixed Cage Spinner Mechanical - 1 11/16 in.

The Fixed Cage Spinner Mechanical (FCSM01,02,04) is run in combination with the 1 11/16 inch FLTE (Flow & Temperature Electronics) which combines the flowmeter sensor electronics with a fast response temperature tool or with our 1 11/16 inch CFT (combined Capacitance, Flow & Temperature) tool. The size is selected depending on the minimum restriction in the completion. The impeller assembly is protected minimizing the likelihood of damage in hole.

Ratings & Dimensions

	FCSM01	FCSM02	FCSM04
Max temperature	350°F (177°C)		
Max pressure	15,000 psi (103.4 mPa)		
Cage diameter	1.69 in (43.0 mm)	2.13 in (54 mm)	3.15 in (80 mm)
Length	6.5 in (165 mm)	6.9 in (175 mm)	7.5 in (191 mm)
Weight	1.4 lb (0.65 kg)	1.6 lb (0. kg)	2.2 lb (1 kg)
Materials	Corrosion resistant materials used throughout		

Measurements

Output	10 pulses per revolution
Threshold	<5 ft /min (1.5 m /min)
Range	Better than 1,500 ft/min
Maximum RPS	200 rps – 4,000 ft/min (measured by FLTE or CFT)

Hardware Characteristics

Combinability	All HD tools (RADii, iQ, PL, RAS, etc.) when connected to FLTE & CFT	
Acquisition Mode	Real-time (with TCU)	Memory (with MLT)

© Copyright 1994-2020 Probe Technologies Holdings, Incorporated. All Rights Reserved. Specifications may change without notice. | FCSM01,02,04