ONLINE TECHNICAL SPECIFICATION SHEET



PERMANENT GAUGE SOLID MANDREL





SKU: AN001-100-217

Categories: Advanced Monitoring, Downhole Instrumentation, KPerm™,

Kuster®, Mandrels, Well Monitoring

PRODUCT DESCRIPTION

The permanent gauge solid mandrel is designed to connect the gauge onto the production tubing and to provide a path for the gauge to measure the internal tubing pressure. The tubing pressure is measured via a port leading to the inside of the production tubing. During the installation of the gauge the mandrel provides full protection for the gauge and the cable head.

The mandrel design makes it suitable for both single and dual pressure permanent gauges. The I.D of the mandrel is the same as the production tubing; the OD can vary depending on the tubing and casing size. All designs are made to meet production-tubing specifications and manufactured in accordance to API 5CT, the tables below provide details for the 3 most common mandrel sizes.

Ratings & Dimensions

Mandrel size
Max pressure
Outer diameter
Inner diameter
Length

Materials
Threaded Connections

Applications

Weight

Mandrel size Max pressure Outer diameter Inner diameter Length

Weight Materials 4-1/2" Mandrel

15,000 psi 5.91 in (15.0 cm) 3.875 in (9.84 cm) 70.0 in (1.77 m) 48.0 lbs (21.77 kg)

CS-4140 – 13Cr; other materials on request EUE / VAM TOP – other threads on request

Piezo, Quartz KPerm gauges

3-1/2" Mandrel

15,000 psi 5.0 in (12.7 cm) 2.92 in (7.41 cm) 67.0 in (1.70 m) 38.0 lbs (17.20 kg)

CS-4140 - 13Cr; other materials on request

ONLINE TECHNICAL SPECIFICATION SHEET



Threaded Connections

Applications

EUE / VAM TOP - other threads on request

Piezo, Quartz KPerm gauges

Mandrel size Max pressure Outer diameter

Outer diameter Inner diameter

Length Weight Materials

Threaded Connections

Applications

2-7/8" Mandrel

15,000 psi

4.50 in. (11.43 cm) 2.40 in. (6.09 cm) 66.0 in. (1.67m) 33.0 lbs (14.97 kg)

CS-4140 – 13Cr; other materials on request EUE / VAM – other threads on request

Piezo, Quartz KPerm gauges

Version Control: 2021.12.14

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.