## ONLINE TECHNICAL SPECIFICATION SHEET



### **TUNING FORK DENSITY TOOL - HD - 1 11/16 IN.**





SKU: TFD001

Categories: Cased Hole Wireline, Fluid Density, HD Platform™, Production

Logging

### PRODUCT DESCRIPTION

The Tuning Fork Density Tool (TFD001) is an HD Platform non-radioactive fluid identification tool that is not affected by well inclination. It provides an industry-standard Fluid Density measurement based on vibrating fork technology.

Optimized for either pure gas or oil-water environments, it can also function as a useful free gas indicator.

#### **Ratings & Dimensions**

**Max Temperature** 350°F (177°C)

 Max Pressure
 15,000 psi (103.4 mPa)

 Diameter
 1.69 in (43.0 mm)

 Length
 30.27 in (769.0 mm)

 Weight
 9.5 lb (4.3 kg)

**Tensile Strength** 15,000.0 lbf (6,803.9 kgf)

**Measure Point** 6.9 in (175.0 mm) from bottom of tool

Materials Corrosion resistant materials used throughout

#### Measurements

**Sensor** Acoustic

**Range** 0 to 1.25 g/cc or better **Accuracy** +/-0.03 g/cc or better

**Resolution** 0.03 g/cc **Response Time** 0.03 g/cc

#### **Hardware Characteristics**

Combinability All HD tools: GR, CCL, iQ, RADii, RAS, PLT

Tool Positioning Centralized

# ONLINE TECHNICAL SPECIFICATION SHEET



Acquisition ModeReal-time (with TCU)

Memory (with MLT)

**Electrical Specification** 

 Voltage
 50V DC
 19V DC

 Current
 20 mA
 50 mA

Version Control: 2021.11.17

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.